



12-503C2

WA-503 LED BEACON

DESCRIPTION

20 PCS SMD LED
 Low Current Draw Consumption
 PC Lens with Smooth Exterior Will Not Gather Dirt and Dust
 Uniform 360 Degree Light Distribution---No Dark Spots
 Magnetic Mount Use Up to 50mph/80kph
 With Cigar Plug

VOLTAGE

10-30V

MOUNT

DIN POLE

CURRENT CONSUMPTION

Peak: 10W/ Average: 6W

APPROVALS

ECE R10(EMC)/ SAE CLASS 3

LENS COLOR

Clear or Color

WARRANTY

3 years

WATERPROOF

IP 67

OPERATING TEMPERATURE

-40°C to +65°C

SEALING

Silica gel

PACKAGING

Net Weight: ____ KG Innerbox: ____ mm
 Outer Packing Carton: ____ mm Packing Qty: 20PCS/CTN



PART NUMBER	LED COLOR	MOUNT	APPROVALS	LEDs	OUTER LENS COLOR
12-503C2A-E		Din Pole mounting	ECE R10(EMC)	20PCS 0.2W SMD AMBER	Clear or Color
12-503C2B-E			ECE R10(EMC)	20PCS 0.2W SMD BLUE	
12-503C2R-E			ECE R10(EMC)	20PCS 0.2W SMD RED	
12-503C2W-E			ECE R10(EMC)	20PCS 0.2W SMD WHITE	
12-503C2A-S		Din Pole mounting	SAE Class 3	20PCS 0.2W SMD AMBER	Clear or Color

FLASH PATTERNS

Flash patterns	FPM (Flashes per minute)
Rotate	188

