



12-703C3

WA-703 LED BEACON

DESCRIPTION

12 PCS SMD LED
Low Current Draw Consumption
PC Lens with Smooth Exterior Will Not Gather Dirt and Dust
Uniform 360 Degree Light Distribution---No Dark Spots
Magnetic Mount Use Up to 50mph/80kph
With Cigar Plug

VOLTAGE

10-30V

MOUNT

3 Sets Magnets/ Three Bolts/ Flat Pipe/ Surface Mount

CURRENT CONSUMPTION

Peak: 36W/ Average: 18W

APPROVALS

ECE R65(AMBER)/ R10(EMC)/ SAE CLASS 1

LENS COLOR

Clear or Color

WARRANTY

3 years

WATERPROOF

IP 67

OPERATING TEMPERATURE

-40°C to +65°C

SEALING

0.5m

PACKAGING



Net Weight:0.586kg Innerbox: 170*170*138mm

Outer Packing Carton: 870*355*298mm Packing Qty: 20PCS/CTN



PART NUMBER	LED COLOR	MOUNT	APPROVALS	LEDs	OUTER LENS COLOR
12-703C3A-E		3 Sets Magnets/ Three Bolts/ Surface Mount	ECE R65/R10(EMC)	12PCS 3W SMD AMBER	Clear or Color
12-703C3B-E			ECE R10(EMC)	12PCS 3W SMD BLUE	
12-703C3R-E			ECE R10(EMC)	12PCS 3W SMD RED	
12-703C3W-E			ECE R10(EMC)	12PCS 3W SMD WHITE	
12-703C3A-S		3 Sets Magnets/ Three Bolts/ Surface Mount	SAE J845 Class 1	12PCS 3W SMD AMBER	Clear or Color
12-703C3B-S			SAE J845 Class 1	12PCS 3W SMD BLUE	
12-703C3R-S			SAE J845 Class 1	12PCS 3W SMD RED	
12-703C3W-S			SAE J845 Class 1	12PCS 3W SMD WHITE	



Surface Mount





FLASH PATTERNS

NO.	Flash patterns	FPM (Flashes per minute)
1	Single 1	150
2	Single 2	75
3	Double 1	150
4	Double 2	75
5	Triple	73
6	Quad	73
7	Front-Rear(split) 1	150
8	Front-Rear(split) 2	75
9	Rotate 1	150
10	Rotate 2	75

Magnets



Surface Mount



Three Bolts

