


12-705C3
WA-705 LED BEACON
DESCRIPTION

36 PCS SMD LED
 Low Current Draw Consumption
 PC Lens with Smooth Exterior Will Not Gather Dirt and Dust
 Uniform 360 Degree Light Distribution---No Dark Spots
 Magnetic Mount Use Up to 50mph/80kph
 With Cigar Plug

VOLTAGE

10-30V

MOUNT

3 Sets Magnets/ Three Bolts/ Flat Pipe/ Surface Mount

CURRENT CONSUMPTION

Peak: 40W/ Average: 18W

APPROVALS

ECE R65(AMBER)/ R10(EMC)/ SAE CLASS 1

LENS COLOR

Clear or Color

WARRANTY

3 years

WATERPROOF

IP 67

OPERATING TEMPERATURE

-40°C to +65°C

SEALING

0.5m

PACKAGING



Net Weight: 1.34KG Innerbox: 170*170*180mm

Outer Packing Carton: 870*355*382mm Packing Qty: 20PCS/CTN



PART NUMBER	LED COLOR	MOUNT	APPROVALS	LEDs	OUTER LENS COLOR
12-705C3A-E		3 Sets Magnets/ Three Bolts/Flat Pipe/ Surface Mount	ECE R65/R10(EMC)	36PCS 0.5W SMD AMBER	Clear or Color
12-705C3B-E			ECE R10(EMC)	36PCS 0.5W SMD BLUE	
12-705C3R-E			ECE R10(EMC)	36PCS 0.5W SMD RED	
12-705C3W-E			ECE R10(EMC)	36PCS 0.5W SMD WHITE	
12-705C3A-S		3 Sets Magnets/ Three Bolts/Flat Pipe/ Surface Mount	SAE J845 Class 1	36PCS 0.5W SMD AMBER	Clear or Color
12-705C3B-S			SAE J845 Class 1	36PCS 0.5W SMD BLUE	
12-705C3R-S			SAE J845 Class 1	36PCS 0.5W SMD RED	
12-705C3W-S			SAE J845 Class 1	36PCS 0.5W SMD WHITE	



Surface Mount


FLASH PATTERNS

Flash patterns	FPM (Flashes per minute)
Double	74
Triple	76
Quad	75
Rotate	143

Magnets

Three Bolts



Flat Pipe

