



12-709C3

WA-709 LED BEACON

DESCRIPTION

36 PCS SMD LED
Low Current Draw Consumption
PC Lens with Smooth Exterior Will Not Gather Dirt and Dust
Uniform 360 Degree Light Distribution---No Dark Spots
Magnetic Mount Use Up to 50mph/80kph
With Cigar Plug

VOLTAGE

10-30V

MOUNT

DIN POLE

CURRENT CONSUMPTION

Peak: 40W/ Average: 18W

APPROVALS

ECE R65(AMBER)/ R10(EMC)/ SAE CLASS 1

LENS COLOR

Clear or Color

WARRANTY

3 years

WATERPROOF

IP 67

OPERATING TEMPERATURE

-40°C to +65°C

SEALING

Silica gel

PACKAGING

Net Weight: ___KG Innerbox: 150*150*192mm
Outer Packing Carton: 468*315*405mm Packing Qty: 12PCS/CTN



PART NUMBER	LED COLOR	MOUNT	APPROVALS	LEDs	OUTER LENS COLOR
12-709C3A-E		Din Pole mounting	ECE R65/R10(EMC)	36PCS 0.5W SMD AMBER	Clear or Color
12-709C3B-E			ECE R10(EMC)	36PCS 0.5W SMD BLUE	
12-709C3R-E			ECE R10(EMC)	36PCS 0.5W SMD RED	
12-709C3W-E			ECE R10(EMC)	36PCS 0.5W SMD WHITE	

FLASH PATTERNS

Flash patterns	FPM (Flashes per minute)
Single or Rotate	150 or 100

