



12-506C2

WA-506 LED BEACON

DESCRIPTION

24 PCS SMD LED
Low Current Draw Consumption
PC Lens with Smooth Exterior Will Not Gather Dirt and Dust
Uniform 360 Degree Light Distribution---No Dark Spots
Magnetic Mount Use Up to 50mph/80kph
With Cigar Plug

VOLTAGE

10-30V

MOUNT

DIN POLE

CURRENT CONSUMPTION

Peak: 10W/ Average: 6W

APPROVALS

ECE R10(EMC)/ SAE CLASS 2

LENS COLOR

Clear or Color

WARRANTY

3 years

WATERPROOF

IP 67

OPERATING TEMPERATURE

-40°C to +65°C

SEALING

Silica gel

PACKAGING

Net Weight: __KG Innerbox: 119*119*194MM
Outer Packing Carton: 620*253*408mm Packing Qty: 20PCS/CTN



PART NUMBER	LED COLOR	MOUNT	APPROVALS	LEDs	OUTER LENS COLOR
12-506C2A-E		Din Pole mounting	ECE R10(EMC)	24PCS 0.2W SMD AMBER	Clear or Color
12-506C2B-E			ECE R10(EMC)	24PCS 0.2W SMD BLUE	
12-506C2R-E			ECE R10(EMC)	24PCS 0.2W SMD RED	
12-506C2W-E			ECE R10(EMC)	24PCS 0.2W SMD WHITE	
12-506C2A-S		Din Pole mounting	SAE Class 2	24PCS 0.2W SMD AMBER	Clear or Color

FLASH PATTERNS

Flash patterns	FPM (Flashes per minute)
Single or Rotate	150 or 100

