



12-608C2

WA-608 LED BEACON

DESCRIPTION

32 PCS SMD LED
 Low Current Draw Consumption
 PC Lens with Smooth Exterior Will Not Gather Dirt and Dust
 Uniform 360 Degree Light Distribution---No Dark Spots
 Magnetic Mount Use Up to 50mph/80kph
 With Cigar Plug

VOLTAGE

10-30V

MOUNT

DIN POLE

CURRENT CONSUMPTION

Peak: 28W/ Average: 16W

APPROVALS

ECE R65(AMBER)/ R10(EMC)/ SAE CLASS 1

LENS COLOR

Clear or Color

WARRANTY

3 years

WATERPROOF

IP 67

OPERATING TEMPERATURE

-40°C to +65°C

SEALING

Silica gel

PACKAGING

Net Weight: KG Innerbox: 168*168*153mm
 Outer Packing Carton: 528*352*327mm Packing Qty: 12PCS/CTN



PART NUMBER	LED COLOR	MOUNT	APPROVALS	LEDs	OUTER LENS COLOR
12-608C2A-E		Din Pole mounting	ECE R65/R10(EMC)	32PCS 0.5W SMD AMBER	Clear or Color
12-608C2B-E			ECE R10(EMC)	32PCS 0.5W SMD BLUE	
12-608C2R-E			ECE R10(EMC)	32PCS 0.5W SMD RED	
12-608C2W-E			ECE R10(EMC)	32PCS 0.5W SMD WHITE	
12-608C2A-S		Din Pole mounting	SAE J845 Class 1	32PCS 0.5W SMD AMBER	Clear or Color
12-608C2B-S			SAE J845 Class 1	32PCS 0.5W SMD BLUE	
12-608C2R-S			SAE J845 Class 1	32PCS 0.5W SMD RED	
12-608C2W-S			SAE J845 Class 1	32PCS 0.5W SMD WHITE	

FLASH PATTERNS

Flash patterns	FPM (Flashes per minute)
Single	150
Double	74
Triple	76
Quad	75
Rotate	143

