






WA0123

FEATURES

- The product meets EMC R10, CISPR 25 Class 5 requirements.
- More connections available in Din-Pole, cable, 2500 mm cigar plug, to meet customer needs in different occasions.
- High IP Protection class IP67, Vibration-resistant ISO 16750-3 Test VII standard (Except for installation of smoke pipe), allow the lamp work in extreme weather.



WA0123CAES-001 (SCREW)




WA0123CAES-002 (MAGNET)

Warning Lamp



WA0123



WA0123CAES-003 (DIN-POLE: TPE)

FLASH PATTERN WA0123CAES-001 WA0123CAES-002		FLASH PATTERN WA0123CAES-003	
#1	Single Flash, Cycle: 400 ms	#1	Rotated, Cycle: 400 ms
#2	Double Flash, Cycle: 800 ms		
#3	Triple Flash, Cycle: 760 ms		
#4	Quad Flash, Cycle: 800 ms		
#5	Rotated, Cycle: 400 ms		

Part NO.	FUNCTION	VOLTAGE	POWER	MATERIAL	MOUNTING	CONNECTION	APPROVALS	MECHANICAL PERFORMANCE
WA0123CAES-001	Amber Warning Lamp	DC 10-30 V	30 W	Cover: PC Lens: PC Housing: PC	Screw	280 mm Cable	ECE R65 Class 1/ SAE J845 Class 1/ CISPR 25 Class 5/ EMC R10	Vibration: RMS=5.79 G 10~2000 Hz Mechanical shock: 30 G
WA0123CAES-002					Magnet	2500 mm Cable With Cigar Plug		
WA0123CAES-003					DIN-Pole: TPE (W/ O Switch)	Connector		

Warning Lamp