



JGP-703C3W

QDP-703C3W

703 Auxilliary Lighting

DESCRIPTION

Low Current Consumption;
Connection form: Cable Length, L = 550 mm
Lens material: PC, UV curing
Garland: ABS, chrome plated, AL die cost housing.

VOLTAGE

10-30V

POWER CONSUMPTION

Spot/Driving Beam: 40W; Front Position: 1.6W;

MOUNT

Bracket installation

LENS COLOUR

Clear

WARRANTY

3 years

WATERPROOF

IP 67

OPERATING TEMPERATURE

-40°C to +65°C

CABLE LENGTH

0.55M

PACKAGING

Net Weight: 1.44KG Innerbox: 203*191*90mm
Outer Packing Carton: 405*228*295mm Packing Qty: 6PCS/CTN



JGP-703C3W



QDP-703C3W

PART NUMBER	FUNCTION	APPROVALS	LEDs	POWER
JGP-703C3W	Spot Beam Front Position	ECE R112/R7/R10	4PCS 10W SMD White LED 8PCS 0.2W SMD White LED	S/D Beam: 40W; FrP: 1.6W;
QDP-703C3W	Driving Beam Front Position		4PCS 10W SMD White LED 8PCS 0.2W SMD White LED	

JGP-703

QDP-703

