



## 12-30C2A-M22

### DESCRIPTION

- 24 PCS SMD LED
- Low Current Draw Consumption
- PC Lens with Smooth Exterior Will Not Gather Dirt and Dust
- Uniform 360 Degree Light Distribution---No Dark Spots
- Low-Profile.

VOLTAGE 10-30V

POWER CONSUMPTION 8 W

MOUNT M22 Single Bolt

APPROVALS SAE J845 CLASS 3

FLASH PATTERN ON TIME:0.13S OFF TIME:0.27S

LENS COLOR Clear and Color

WARRANTY 3 Years

WATERPROOF IP 67

OPERATING TEMPERATURE -40° C to +65° C



PACKAGING

## WA-538 LED BEACON

Net Weight:0.185KG Innerbox:102\*82\*115mm  
Outer Packing Carton:538\*433\*252mm Packing Qty:50PCS/CTN



| PART NUMBER  | LED COLOUR | MOUNT           | VOLTAGE | LEDs                  | OUTER LENS COLOR |
|--------------|------------|-----------------|---------|-----------------------|------------------|
| 12-30C2A-M22 |            | M22 Single Bolt | 10-80V  | 24 PCS 0.2W SMD Amber | Clear or Color   |
| 12-30C2B-M22 |            |                 |         | 24 PCS 0.2W SMD Blue  |                  |
| 12-30C2R-M22 |            |                 |         | 24 PCS 0.2W SMD Red   |                  |
| 12-30C2W-M22 |            |                 |         | 24 PCS 0.2W SMD White |                  |



## 12-30C2A-ST

### DESCRIPTION

- 24 PCS SMD LED
- Low Current Draw Consumption
- PC Lens with Smooth Exterior Will Not Gather Dirt and Dust
- Uniform 360 Degree Light Distribution---No Dark Spots
- Low-Profile.

VOLTAGE 10-30V

POWER CONSUMPTION 8 W

MOUNT ST 5

APPROVALS SAE J845 CLASS 3

FLASH PATTERN ON TIME:0.13S OFF TIME:0.27S

LENS COLOR Clear and Color

WARRANTY 3 Years

WATERPROOF Ip67

OPERATING TEMPERATURE -40° C to +65° C

PACKAGING

## WA-539 LED BEACON

Net Weight:0.185KG Innerbox:102\*82\*115mm  
Outer Packing Carton:538\*433\*252mm Packing Qty:50PCS/CTN



| PART NUMBER | LED COLOUR | MOUNT     | VOLTAGE | LEDs                  | OUTER LENS COLOR |
|-------------|------------|-----------|---------|-----------------------|------------------|
| 12-30C2A-ST |            | 2 PCS ST5 | 10-80V  | 24 PCS 0.2W SMD Amber | Clear or Color   |
| 12-30C2B-ST |            |           |         | 24 PCS 0.2W SMD Blue  |                  |
| 12-30C2R-ST |            |           |         | 24 PCS 0.2W SMD Red   |                  |
| 12-30C2W-ST |            |           |         | 24 PCS 0.2W SMD White |                  |

